

## Dynamometric key set WBT-0490

with torque controlled screwdriver and 4-mm bits

WBT

## WBT-0490 Drehmomentschraubendreher-Set

mit drehmomentkontrolliertem Schraubendreher und 4-mm-Bits



## Dynamometric key set WBT-0490

with torque controlled screwdriver and 4-mm bits

The Dynamometric key is simply a joy for every professional user but also enthusiastic hobby mechanics and repairers of devices such as watches, model railways, cameras and spectacles etc. WBT-0481 is a solid metal tool in machine construction quality with an extremely elegant design as well as perfect handling features and ergonomomy.

The adjustable torque of the Dynamometric key always permits a precise operation at controlled maximum pressure. It is factory pre-set to 0.5 Nm and so mostly suitable for e.g. the perfect installation of WBT connectors, but also for many other purposes. The WBT-0490 set is available with 18 different 4-mm bits, all made of hardened chrome vanadium steel, finished in high quality and so ensuring an extremely long service. A spring action ball acting as a pressure piece guarantees an easy change of the bits when required. For this purpose the bit is to be grabbed with the thumb and forefinger and pulled with one heave out of the shaft. The new bit is to be pushed all the way down till the spring action ball engages perceptibly.



### Torx T.6 test bolt

If you have never worked with a precision torque screwdriver we suggest testing your new tool using the test bolt available with this set. To do so take the Torx T.6 bit out of your bit assortment and start screwing the screw in the test bolt. When the torque of 0.5 Nm has been reached you will hear the screwdriver buzz. The screwdriver interrupts its action immediately.

### The Bit assortment

The list of the assortment includes the following bits:

4 x slot-head	blade width in mm:	4 x cross-recess	cross size	
WBT-0485.S1	1.5	WBT-0485.P1	000	
WBT-0485.S2	2.0	WBT-0485.P2	00	
WBT-0485.S3	2.5	WBT-0485.P3	0	
WBT-0485.S4	3.0	WBT-0485.P4	1	
4 x torx	torx size	6 x hex head	size in mm	in inches
WBT-485.T1	T. 6	WBT-0485.H1	1.3	0.050
WBT-485.T2	T. 7	WBT-0485.H2	1.5	–
WBT-485.T3	T. 8	WBT-0485.H3	–	1/16
WBT-485.T4	T.10	WBT-0485.H4	2.0	5/64
Further bits are available (upon request)!		WBT-0485.H5	–	3/32
		WBT-0485.H6	2.5	–

Detailed product information available.  
Design and specifications subject to change without notice.

© WBT-Distribution GmbH · Im Teelbruch 103 · 45219 Essen · Germany  
Tel.: +49 (0) 2054 87 552-0 · Fax: +49 (0) 2054 87 552-22  
e-mail: info@wbt.de · Internet: www.wbt.de